12~24VDC

UR06 LED FLUSH MOUNT KIT





















FEATURES

- Classic UR series is now available in Dual Colour.
- Multi-memories design for instant switch between selected flash patterns and/or colours.
- Heavy-duty design with waterproof connectors.
- 2 heads to 1 flash controller for easy set-up and installation.
- Multi-Voltage Input 12~24VDC.
- Multi units synchronization in simultaneous or alternating flash.
- Reverse polarity protection.
- Fully weatherproof and vibration resistant lighthead design for exterior or interior use.

SPECIFICATIONS

Compliance: SAE J595 Class 1, ECE R10, IPX7

LED Element: High intensity LED x 12 No. of Warning Patterns: 27 Flash Patterns

Operating Voltage: 12~24 VDC

Avg. Current: 0.55A @12VDC / 0.28A @24VDC

(varies with flash pattern)

Avg. Power: 6.6W

(varies with flash pattern)

Max. Current: 1.1A @12VDC / 0.55A @24VDC

Max. Power: 13.2W

Wires: Red-Vcc: 180cm (20AWG) Black-GND: 180cm (20AWG)

Yellow-Flash Patterns & Sync: 180cm (20AWG)

White-Phase: 180cm (20AWG) Cable Lengths: Output: 79cm (24AWG)

Extension: 200cm (24AWG) Lighthead: 18cm (24AWG)

Max. Cable Lengths: Controller Cable = 450cm Lighthead Cable = 780cm

Fuse Rating: 2A


Synchronization: Over 15 units

LED Colour: Amber, Blue, Green, Red, White

Lens Colour: Clear

DIMENSIONS

Lighthead





LED Controller





FLASH PATTERNS

Flash Patterns						
1	Double	[2Hz]		15	Random	
2	Single	[2Hz]		16	Double	[2Hz] (Split)
3	Triple	[2Hz]		17	Single	[2Hz] (Split)
4	Quad	[2Hz]		18	Triple	[2Hz] (Split)
5	Single			19	Quad	[2Hz] (Split)
6	Double			20	Single	(Split)
7	Quad			21	Double	(Split)
8	Quint			22	Quad	(Split)
9	Mega			23	Quint	(Split)
10	Ultra			24	Mega	(Split)
11	Single-Quad			25	Ultra	(Split)
12	Single H/L		26	Single-Quad	(Split)	
13	Steady EF *			27	Single H/L	(Split)
14	Steady Scene					

(Split) = Head 1 alternating Head 2.

PART No.

■ **F017-1B3xy-000** (SAE Class 1) ■ F017-2B3xy-000 (ECE R10)

Replace x, y for colour (x for lighthead 1, y for lighthead 2):

E = Amber/Green LED J = Red/Amber LED K = Amber/White I FD Q = Red/Blue I FD D = Blue/Amber I FD U = Red/White I FD T = Blue/White LED

OPTIONAL ACCESSORIES

02060323

(Single L-Bracket)





^{*} For use with external flasher controller.