

# TR3 Traffic Rayzr

## Warning Light Stick



E10-402XX-00

### FEATURES

- Super Low Profile for stealth look.
- LEDs rated to 100,000 hours of operation.
- Aluminium extrusion for heat dissipation.
- Non-volatile memory recalls last flash pattern used at power up.
- Reverse polarity protection.
- Lightheades come with waterproof connectors for quick and easy replacement.

### SPECIFICATIONS

**Compliances:** SAE J595, SAE J845, CA13 R/B, ECE R10.

**No. of Flash Patterns:** 27 Warning Patterns

**Operating Voltage:** 12~24VDC

**Avg. Current:** 4 Heads = 1A @12.8VDC / 0.5A @ 24VDC  
(varies with flash pattern)

**Avg. Power:** 4 Heads = 12.2Watts  
(varies with flash pattern)

**Max. Current:** 4 Heads = 1.9A @12.8VDC / 1A @ 24VDC

**Max. Power:** 4 Heads = 24.4Watts

**Storage Temp.:** -40°C to +75°C

**Operating Temp.:** -30°C to +65°C

**LED Colour:** Amber, Blue, Red, White

### DIMENSIONS

**Length:** 457.8mm (18.02")

**Height:** 24mm (0.95")

**Depth:** 38mm (1.50")

### FLASH PATTERN

Flash Patterns	
1	Kit Scan
2	Kit Scan + Double Flash
3	Wig-Wag Slow-Fast
4	Outside-In Single
5	Outside-In Ultra
6	Side-by-Side Single
7	Side-by-Side Ultra
8	Side-by-Side Slow-Fast
9	Random
10	Single (split) [SAE]
11	Double (split) [2Hz]
12	Quint (split) [SAE]
13	Ultra (split) [SAE]
14	Single-Quad (split)
15	Single H/L (split)
16	Quint (split) + Mega (all)
17	Single [SAE]
18	Double 2Hz
19	Quint [SAE]
20	Ultra [SAE]
21	Single-Quad
22	Single H/L
23	Quint (all) + Mega (split)
24	Steady Half
25	Steady All
26	Left Chaser
27	Right Chaser